

AMENDMENTS TO THE CLAIMS

1. (PREVIOUSLY PRESENTED) An apparatus comprising:

a first circuit configured to acquire a current picture,
a first reference picture and a second reference picture;

a second circuit configured to generate a measurement of
5 inter-picture motion between said current picture and said first
reference picture by performing a global motion estimation process
on said current picture and said first reference picture;

a third circuit configured to generate a control signal
in response to (i) said measurement of inter-picture motion between
10 said current picture and said first reference picture and (ii) a
predetermined threshold value;

a fourth circuit configured to select either said first
reference picture or said second reference picture as a better
reference picture for subsequent motion estimation and motion
15 compensation on said current picture in response to said control
signal; and

a motion estimation circuit configured to generate one or
more motion vectors in response to said better reference picture
and said current picture, wherein said current picture is encoded
20 based upon said one or more motion vectors.

2. (ORIGINAL) The apparatus according to claim 1,
wherein:

a parity of said first reference picture is opposite to
a parity of said current picture; and

5 a parity of said second reference picture is the same as
said parity of said current picture.

3. (ORIGINAL) The apparatus according to claim 1,
wherein:

a parity of said first reference picture is the same as
a parity of said current picture; and

5 a parity of said second reference picture is opposite to
said parity of said current picture.

4. (ORIGINAL) The apparatus according to claim 1,
further comprising:

a memory configured to store said current picture, said
first reference picture and said second reference picture.

5. (PREVIOUSLY PRESENTED) The apparatus according to
claim 1, wherein said fourth circuit further comprises:

a multiplexer circuit configured to select (i) said first
reference picture for presentation as said better reference picture
5 in response to a first state of said control signal and (ii) said

second reference picture for presentation as said better reference picture in response to a second state of said control signal.

6. (CANCELED).

7. (PREVIOUSLY PRESENTED) The apparatus according to claim 1, wherein said second circuit further comprises:

a low-complexity motion estimation circuit configured to generate a plurality of coarse motion vectors for said current picture based upon a low-resolution inter-picture motion search of said first reference picture.

8. (PREVIOUSLY PRESENTED) The apparatus according to claim 7, wherein said second circuit further comprises:

a first analysis circuit configured to determine a dominant global motion component based upon said coarse motion vectors and generate said measurement of inter-picture motion in response to said dominant global motion component.

9. (PREVIOUSLY PRESENTED) The apparatus according to claim 8, wherein said second circuit further comprises:

a second analysis circuit configured to generate said control signal based upon a fraction of said coarse motion vectors

5 contained in a cluster associated with said dominant global motion
component and said predetermined threshold value.

10. (ORIGINAL) The apparatus according to claim 8,
wherein:

 said first analysis circuit is configured to perform a
cluster analysis on said coarse motion vectors.

11. (ORIGINAL) The apparatus according to claim 1,
wherein said apparatus is part of an encoder circuit.

12. (PREVIOUSLY PRESENTED) An apparatus comprising:
 means for acquiring a current picture, a first reference
picture and a second reference picture;

5 means for generating a measurement of inter-picture
motion between said current picture and said first reference
picture by performing a global motion estimation process on said
current picture and said first reference picture;

 means for generating a control signal in response to (i)
said measurement of inter-picture motion between said current
10 picture and said first reference picture and (ii) a predetermined
threshold value;

 means for selecting either said first reference picture
or said second reference picture as a better reference picture for

subsequent motion estimation and motion compensation on said
15 current picture in response to said control signal; and

means for generating one or more motion vectors in
response to said better reference picture and said current picture,
wherein said current picture is encoded based upon said one or more
motion vectors.

13. (PREVIOUSLY PRESENTED) A method for performing
motion estimation in a video encoder comprising the steps of:

acquiring a current picture, a first reference picture
and a second reference picture;

5 generating a measurement of inter-picture motion between
said current picture and said first reference picture by performing
a global motion estimation process on said current picture and said
first reference picture;

generating a control signal in response to (i) said
10 measurement of inter-picture motion between said current picture
and said first reference picture and (ii) a predetermined threshold
value;

selecting either said first reference picture or said
second reference picture as a better reference picture for
15 subsequent motion estimation and motion compensation on said
current picture in response to said control signal; and

generating one or more motion vectors in response to said better reference picture and said current picture, wherein said current picture is encoded based upon said one or more motion vectors.

14. (ORIGINAL) The method according to claim 13, wherein:

a parity of said first reference picture is opposite to a parity of said current picture; and

a parity of said second reference picture is the same as said parity of said current picture.

15. (ORIGINAL) The method according to claim 13, wherein:

a parity of said first reference picture is the same as a parity of said current picture; and

a parity of said second reference picture is opposite to said parity of said current picture.

16. (ORIGINAL) The method according to claim 13, further comprising the step of:

storing said current picture, said first reference picture and said second reference picture in a picture memory.

17. (CANCELED) .

18. (PREVIOUSLY PRESENTED) The method according to claim 13, further comprising the step of:

generating a plurality of coarse motion vectors for said current picture based upon a low-resolution inter-picture motion search of said first reference picture.

19. (PREVIOUSLY PRESENTED) The method according to claim 18, further comprising the steps of:

determining a dominant global motion component based upon said coarse motion vectors; and

generating said measurement of inter-picture motion in response to said dominant global motion component.

20. (PREVIOUSLY PRESENTED) The method according to claim 19, further comprising the step of:

generating said control signal having (i) a first state in response to said measurement of inter-picture motion exceeding said predetermined threshold value and (ii) a second state in response to said measurement of inter-picture motion not exceeding said predetermined threshold value.

21. (ORIGINAL) The method according to claim 19, further comprising:

performing a cluster analysis on said coarse motion vectors.

22. (ORIGINAL) The method according to claim 13, wherein said current picture, said first reference picture and said second reference picture each comprise a field picture.

23. (PREVIOUSLY PRESENTED) The method according to claim 13, wherein said predetermined threshold value is programmable.

24. (PREVIOUSLY PRESENTED) The apparatus according to claim 1, wherein said first reference picture comprises a temporally closest reference picture to said current picture.

25. (NEW) The method according to claim 19, further comprising the step of:

generating said control signal based upon a fraction of said coarse motion vectors contained in a cluster associated with said dominant global motion component and said predetermined threshold value.